



## Technical data

- Special PVC control cables Adapted to DIN VDE 0276 part 627, DIN VDE 0281 part 13, with insulation thickness for 1 kV type and UL-Std. 758 Style 21179
- **Temperature range**  
flexing -5 °C to +80 °C  
fixed installation -40 °C to +80 °C
- **Nominal voltage** 1000 V
- **Test voltage** 4000 V
- **Breakdown voltage** min. 8000 V
- **Insulation resistance**  
min. 20 MOhm x km
- **Power rating**  
as per DIN VDE 0298
- **Minimum bending radius**  
flexing 7,5x cable ø  
fixed installation 4x cable ø
- **Radiation resistance**  
up to 80x10<sup>6</sup> cJ/kg (up to 80 Mrad)

## Cable structure

- Bare copper, fine wire conductors, as per DIN VDE 0295 cl. 5, BS 6360 cl. 5 and IEC 60228 cl. 5
- Special PVC core insulation TI2, to DIN VDE 0281 part 1, class 43 UL-Std. 1581
- Black cores with white figure imprints to DIN VDE 0293
- Green-yellow earth core in the outer layer (3 cores and above)
- Cores stranded in layers with optimal lay-length
- Separating foil Special PVC outer sheath TM2, to DIN VDE 0281 part 1, class 43 UL-Std. 1581
- Colour black (RAL 9005) or grey (RAL 7001)
- with meter marking, change-over in 2011

## Properties

- Extensively oil resistant, oil-/ chemical Resistance - see table Technical Informations
- Resistant to ultra violet rays (building with black jacket)
- PVC self-extinguishing and flame retardant according to VDE 0482-332-1-2, DIN EN 60332-1-2/ IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B) VW1, FT1
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

## Note

- G = with green-yellow earth core;  
x = without green-yellow earth core (OZ).
- AWG sizes are approximate equivalent values. The actual cross-section is in mm<sup>2</sup>.
- **screened analogue type:**  
**JZ-600-Y-CY UL/CSA**, see page N 20

## Application

Wiring cable for measuring and controlling purposes in tool machinery, conveyor belts and production lines, for plant installations, air conditioning and in steel production plants and rolling mills. Suitable for installation for flexible use for medium mechanical stresses with free movement without tensile stress or forced movements in dry, moist and wet rooms as well as outside (fixed installation, building with black jacket). Is not suitable to be used as direct burial- or as underwater cable. The cores have been numbered in such a way that the numbers are easily identifiable, even if the cable has only been stripped back a few cm. The core numbers have been underlined to avoid confusion. The earth core is located in the outer layer. The black, special PVC outer sheath is resistant to the ultra violet radiation. Mainly used in South-European, Eastern and Arabian countries.

CE= The product is conformed with the EC Low-Voltage Directive 2006/95/EG.

Part no.	No. cores x cross-sec. mm <sup>2</sup>	AWG-No.	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km
Jacket colour black					
11815	2 x 0,5	20	6,4	9,6	56,0
11816	3 G 0,5	20	6,8	14,4	68,0
11817	4 G 0,5	20	7,6	19,0	100,0
11818	5 G 0,5	20	8,2	24,0	117,0
11819	7 G 0,5	20	9,8	33,6	138,0
11820	12 G 0,5	20	12,2	58,0	200,0
11821	18 G 0,5	20	14,4	86,0	276,0
11822	25 G 0,5	20	17,2	120,0	335,0
11823	2 x 0,75	19	6,8	14,4	66,0
11824	3 G 0,75	19	7,2	21,6	74,0
11825	4 G 0,75	19	8,0	29,0	126,0
11826	5 G 0,75	19	8,8	36,0	140,0
11827	7 G 0,75	19	10,7	50,0	190,0
11828	12 G 0,75	19	13,1	86,0	257,0
11829	18 G 0,75	19	15,6	130,0	362,0
11830	25 G 0,75	19	18,9	180,0	486,0
11831	2 x 1	18	7,4	19,2	80,0
11832	3 G 1	18	8,0	29,2	96,0
11833	4 G 1	18	8,8	38,4	100,0
11834	5 G 1	18	9,8	48,0	130,0
11835	7 G 1	18	11,7	67,0	170,0
11836	12 G 1	18	14,5	115,0	290,0
11837	18 G 1	18	17,3	173,0	405,0
11838	25 G 1	18	21,1	240,0	570,0
11839	2 x 1,5	16	8,4	29,0	95,0
11840	3 G 1,5	16	9,1	43,0	112,0
11841	4 G 1,5	16	9,9	58,0	139,0
11842	5 G 1,5	16	11,0	72,0	170,0
11843	7 G 1,5	16	13,3	101,0	225,0
11844	12 G 1,5	16	16,6	173,0	370,0
11845	18 G 1,5	16	19,7	259,0	520,0
11846	25 G 1,5	16	23,9	360,0	730,0

Part no.	No. cores x cross-sec. mm <sup>2</sup>	AWG-No.	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km
Jacket colour grey					
11880	2 x 0,5	20	6,4	9,6	56,0
11881	3 G 0,5	20	6,8	14,4	68,0
11882	4 G 0,5	20	7,6	19,0	100,0
11883	5 G 0,5	20	8,2	24,0	117,0
11884	7 G 0,5	20	9,8	33,6	138,0
11885	12 G 0,5	20	12,2	58,0	200,0
11886	18 G 0,5	20	14,4	86,0	276,0
11887	25 G 0,5	20	17,2	120,0	335,0
11888	2 x 0,75	18	6,8	14,4	66,0
11889	3 G 0,75	18	7,2	21,6	74,0
11890	4 G 0,75	18	8,0	29,0	126,0
11891	5 G 0,75	18	8,8	36,0	140,0
11892	7 G 0,75	18	10,7	50,0	190,0
11893	12 G 0,75	18	13,1	86,0	257,0
11894	18 G 0,75	18	15,6	130,0	362,0
11895	25 G 0,75	18	18,9	180,0	486,0
11896	2 x 1	17	7,4	19,2	80,0
11897	3 G 1	17	8,0	29,2	96,0
11898	4 G 1	17	8,8	38,4	100,0
11899	5 G 1	17	9,8	48,0	130,0
11900	7 G 1	17	11,7	67,0	170,0
11901	12 G 1	17	14,5	115,0	290,0
11902	18 G 1	17	17,3	173,0	405,0
11903	25 G 1	17	21,1	240,0	570,0
11904	2 x 1,5	16	8,4	29,0	95,0
11905	3 G 1,5	16	9,1	43,0	112,0
11906	4 G 1,5	16	9,9	58,0	139,0
11907	5 G 1,5	16	11,0	72,0	170,0
11908	7 G 1,5	16	13,3	101,0	225,0
11909	12 G 1,5	16	16,6	173,0	370,0
11910	18 G 1,5	16	19,7	259,0	520,0
11911	25 G 1,5	16	23,9	360,0	730,0

Continuation ►

# JZ-600 UL/CSA flexible, number coded, 0,6/1kV, meter marking



Part no. Jacket colour black	No. cores x cross-sec. mm²	AWG-No.	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km
11847	2 x 2,5	14	9,4	48,0	160,0
11848	3 G 2,5	14	9,9	72,0	175,0
11849	4 G 2,5	14	11,1	96,0	203,0
11850	5 G 2,5	14	12,4	120,0	251,0
11851	7 G 2,5	14	15,0	168,0	330,0
11852	12 G 2,5	14	18,4	288,0	553,0
11853	18 G 2,5	14	22,0	432,0	795,0
11854	25 G 2,5	14	26,9	600,0	1110,0
11855	2 x 4	12	11,4	77,0	180,0
11856	3 G 4	12	12,3	115,0	230,0
11857	4 G 4	12	13,8	154,0	310,0
11858	5 G 4	12	15,3	192,0	410,0
11859	7 G 4	12	16,8	269,0	540,0
11860	12 G 4	12	22,9	461,0	860,0
11861	3 G 6	10	14,1	173,0	370,0
11862	4 G 6	10	15,6	230,0	430,0
11863	5 G 6	10	17,3	288,0	650,0
11864	7 G 6	10	19,3	403,0	860,0
11865	3 G 10	8	16,5	288,0	660,0
11866	4 G 10	8	18,1	384,0	790,0
11867	5 G 10	8	20,5	480,0	960,0
11868	7 G 10	8	22,5	672,0	1300,0
11869	3 G 16	6	19,6	461,0	760,0
11870	4 G 16	6	21,7	614,0	1100,0
11871	5 G 16	6	24,2	768,0	1600,0
11872	7 G 16	6	25,7	1075,0	1890,0
11873	3 G 25	4	24,0	720,0	1450,0
11874	4 G 25	4	26,9	960,0	1600,0
11875	5 G 25	4	29,4	1200,0	2050,0
11876	7 G 25	4	32,8	1680,0	2900,0

Part no. Jacket colour grey	No. cores x cross-sec. mm²	AWG-No.	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km
11912	2 x 2,5	14	9,4	48,0	160,0
11913	3 G 2,5	14	9,9	72,0	175,0
11914	4 G 2,5	14	11,1	96,0	203,0
11915	5 G 2,5	14	12,4	120,0	251,0
11916	7 G 2,5	14	15,0	168,0	330,0
11917	12 G 2,5	14	18,4	288,0	553,0
11918	18 G 2,5	14	22,0	432,0	795,0
11919	25 G 2,5	14	26,9	600,0	1110,0
11920	2 x 4	12	11,4	77,0	180,0
11921	3 G 4	12	12,3	115,0	230,0
11922	4 G 4	12	13,8	154,0	310,0
11923	5 G 4	12	15,3	192,0	410,0
11924	7 G 4	12	16,8	269,0	540,0
11925	12 G 4	12	22,9	461,0	860,0
11926	3 G 6	10	14,1	173,0	370,0
11927	4 G 6	10	15,6	230,0	430,0
11928	5 G 6	10	17,3	288,0	650,0
11929	7 G 6	10	19,3	403,0	860,0
11930	3 G 10	8	16,5	288,0	660,0
11931	4 G 10	8	18,4	384,0	790,0
11932	5 G 10	8	20,5	480,0	960,0
11933	7 G 10	8	22,5	672,0	1300,0
11934	3 G 16	6	19,6	461,0	760,0
11935	4 G 16	6	21,7	614,0	1100,0
11936	5 G 16	6	24,2	768,0	1600,0
11937	7 G 16	6	25,7	1075,0	1890,0
11938	3 G 25	4	24,0	720,0	1450,0
11939	4 G 25	4	26,9	960,0	1600,0
11940	5 G 25	4	29,3	1200,0	2050,0
11941	7 G 25	4	32,6	1680,0	2900,0

Dimensions and specifications may be changed without prior notice. (RN01)